

shop & compare Waterproof Loupes




for anyone who needs vision enhancement

ROSE MICRO SOLUTIONS



1-800-263-3557
































ROSE MICRO SOLUTIONS





Magnification	Working Distance	Depth of Field	Field of View**	Weight*	Pupillary Adjustment
2.0x (short) 2.0x (regular) 2.0x (long) 2.0x (extra long) 2.0xx (double XL)	11" (280 mm) 12.5" (320 mm) 15.8" (400 mm) 18" (460 mm) 22" (559 mm)	5-8" (125-203mm) 5-8" (125-203mm) 5-8" (125-203mm) 5-8" (125-203mm) 5-8" (125-203mm)	4.33" (110mm) 4.33" (110mm) 4.33" (110mm) 4.33" (110mm) 4.33" (110mm)	2.4 oz. (68.5gm) 2.4 oz. (68.5gm) 2.4 oz. (68.5gm) 2.4 oz. (68.5gm) 2.4 oz. (68.5gm)	2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm)
2.5x (short) 2.5x (regular) 2.5x (medium) 2.5x (long) 2.5x (extra long)	11" (280 mm) 13.8" (350 mm) 16.5" (420 mm) 19.0" (480 mm) 22.0" (559 mm)	3-5" (76-127mm) 3-5" (76-127mm) 3-5" (76-127mm) 3-5" (76-127mm) 3-5" (76-127mm)	3" (76mm) 3" (76mm) 3" (76mm) 3" (76mm) 3" (76mm)	2.2 oz. (63.5gm) 2.2 oz. (63.5gm) 2.2 oz. (63.5gm) 2.2 oz. (63.5gm) 2.2 oz. (63.5gm)	2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm)
3.5x (super short) 3.5x (short) 3.5x (regular) 3.5x (long) 3.5x (extra long)	13.8" (350 mm) 16.53" (420 mm) 19.68" (500 mm)	3-4" (76-101mm) 3-4" (76-101mm) 3-4" (76-101mm) 3-4" (76-101mm) 3-4" (76-101mm)	2.5" (65mm) 2.5" (65mm) 2.5" (65mm) 2.5" (65mm) 2.5" (65mm)	2.1 oz. (61.5gm) 2.1 oz. (61.5gm) 2.1 oz. (61.5gm) 2.1 oz. (61.5gm) 2.1 oz. (61.5gm)	2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm)
	13" (340 mm) 16.53" (420 mm) 19.60" (500 mm)	1.5-2" (38-50mm) 1.5-2" (38-50mm)	2" (51mm) 2" (51mm) 2" (51mm) 2" (51mm) **At maximum I.P.E	3.9 oz. (115gm) 3.9 oz. (115gm) 3.9 oz. (115gm) 3.9 oz. (115gm) 0./ W.D.	2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm) 2-3" (51-76mm)

Limited Lifetime Warranty

Rose Micro Loupes carry a limited lifetime warranty against any manufacturing defects, beginning on the date of purchase (invoice date) from Rose Micro Solutions. This product warranty applies only within the United States of America, Canada, or sale to authorized Dealers or Distributors. Rose Micro will, at its option, repair or replace any product or parts covered by this warranty. The purchaser shall be responsible for shipping and insurance costs to Rose Micro, Buffalo, NY, USA. This warranty is nontransferable and applies to only the original purchaser of this product as determined by Rose Micro sales records. All returns must be authorized. Contact Rose Micro Solutions customer service department and receive a return authorization number. Repackage the product in the original box with all accessories and papers.

Loupe accessories carry a one year warranty against manufacturing defects.

Due to a policy of continued improvement, we reserve the right to change product/specifications without notice.

leadband

oupe Accessories

Rose LED Light

The "Rose Light" is a nice alternative to high priced LED lights. It is light weight and can be adapted to fit any loupe. Solid state LED lamp never needs replacement.

Rose light includes your light, two (2) rechargeable battery packs, eight (8) AA rechargeable batteries, a wall charger, yellow flip filter and padded carry case.

Headlight

 Illuminosity:
 30000 lx (3000 fc)

 Weight:
 14.5g (0.51 oz.)

 Led lifetime:
 50,000 hrs

LED Power Pack

The "Power Pack" is a high power LED Light designed for the professional. It is extremely light weight and can be adapted to fit any loupe. The power pack kit includes your light, two (2) rechargeable battery packs with rheostat control and a lighted battery charge indicator, a wall charger, optional yellow filter and a padded carry case.

Technical specifications:

Headlight

Luminous intensity: 140 lm

Illuminosity: 70,000 Ix (6500 fc)

Color temperature: 6500K

Dimensions: 34 x 28 mm (1.34" x 1.1")

Weight (w/o clip/filter): 7.0g (0.25 oz) Led lifetime: 100,000 hours

Power Pack

Internal battery voltage: 4.8 V Full battery charging time: 120 min Average operating time: 5.5 hours

Dimensions: 97 x 65 x 38mm (3.82" x 2.56" x 1.5")

Weight: 14.5g (0.51 oz)

Charger

Type: Switching AC/DC adaptor

Input voltage: 100 – 240V Input frequency: 50 – 60 Hz Wall outlet plug: Euro/US Output power: 12W

Batteries have a power level indicator

RETURN POLICY

All Rose Micro Solutions optical products are fully inspected for defects in manufacturing and workmanship prior to shipping. Any items returned are subject to a 15% restocking fee.





1-800-263-3557